



US006228527B1

(12) **United States Patent**
Medeiros et al.

(10) **Patent No.:** **US 6,228,527 B1**
(45) **Date of Patent:** **May 8, 2001**

(54) **MAGNESIUM SOLUTION PHASE
CATHOLYTE SEAWATER
ELECTROCHEMICAL SYSTEM**

(75) Inventors: **Maria G. Medeiros**, Bristol; **Steven P. Tucker**, Portsmouth, both of RI (US); **James M. Cichon**, Norwood; **Russell R. Bessette**, Mattapoisett, both of MA (US); **Dwayne W. Dischert**, Newport, RI (US)

(73) Assignee: **The United States of America as represented by the Secretary of the Navy**, Washington, DC (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/267,905**

(22) Filed: **Mar. 2, 1999**

(51) Int. Cl.⁷ **H01M 6/34; H01M 6/30**

(52) U.S. Cl. **429/119; 429/118; 29/623.1; 29/623.5**

(58) Field of Search **429/118, 119; 29/623.1, 623.5**

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,481,266 * 11/1984 Littauer et al. 429/12
4,910,102 * 3/1990 Rao et al. 429/51
4,927,717 * 5/1990 Turley et al. 429/27

5,116,695 * 5/1992 Rao et al. 429/12
5,162,168 * 11/1992 Downing et al. 429/51
5,225,291 * 7/1993 Rao 429/51
5,445,905 * 8/1995 Marsh et al. 429/105
5,718,986 * 2/1998 Brenner 429/105

* cited by examiner

Primary Examiner—Carol Chaney

Assistant Examiner—Tracy Dove

(74) *Attorney, Agent, or Firm*—Michael J. McGowan;
Robert W. Gauthier; Prithvi C. Lall

(57) **ABSTRACT**

In accordance with the present invention, an electrochemical system is provided which comprises a plurality of cells, the cells being formed by spaced apart bipolar electrodes. Each of the electrodes is formed by an anode portion formed from a magnesium containing material and an electrocatalytic material joined to a surface of the anode. The electrodes are spaced such that the anode portion of one electrode faces the electrocatalytic material of the adjacent electrode. The electrochemical system also comprises a manifold system for introducing a seawater-catholyte solution into the spaces between the electrodes. An electrical connection is provided across the cells so as to initiate the reduction of the seawater-catholyte solution at the electrodes and to create electrical power. In a preferred embodiment, the seawater-catholyte solution is a seawater-hydrogen peroxide or seawater-sodium hypochlorite solution. A process for generating electrical power using the electrochemical system of the present invention is also described.

13 Claims, 2 Drawing Sheets

